


MATERIAL LIST

ITEM	QTY	SECTION	LENGTH	GRADE	MASS(kg)
p-1	1	PL10x2000	2800	Q355B	440
p-2	2	PL10x191	2157	Q355B	62
p-3	2	PL10x191	2957	Q355B	80
p-4	1	PL10x2200	3000	Q355B	518
p-5	2	RHS180x100x4	2127	Q355B	71
p-6	2	PL5x180	2957	Q355B	35
p-7	10	PL5x180	945	Q355B	60
p-8	5	PL10x180	1046	Q355B	55
p-9	4	PL5x180	2157	Q355B	56
p-10	2	PL10x180	2157	Q355B	56
p-11	3	PL10x180	2157	Q355B	82
LT-1	4	Outsourced parts(5T)		Q355B	2
37					TOTAL MASS
					1517

TYPE	STEEL CRANE PADS
SIZE	3.0m x 2.2m x 0.19m
RATING	200t

Ground Pressure Rating		
WIDTH (mm)		2200
LENGTH (mm)		3000
CONTACT AREA (m^2)		6.6
GROUND PRESSURE	kg / m^2	kPa
25 TONNE	3773	37 (60)
50 TONNE	7648	75 (120)
100 TONNE	15296	150 (235)
150 TONNE	22944	225 (355)
200 TONNE	30591	300 (470)

NOTE: GROUND PRESSURE VALUES ARE THE MINIMUM ALLOWABLE PRESSURE WHEN THE OUTRIGGER BASE PLATE IS CENTRALLY LOADED. THE VALUES IN THE PARENTHESES ARE THE MINIMUM ALLOWABLE PRESSURE IF REQUIRING OFFSET WITHIN THE LOAD AREA.

UNLESS OTHERWISE STATED		
GENERAL	0.00 = ± 0.05	
TOLERANCES	0.0 = ± 0.2	
ANGLES	0 = ± 0.5°	

THIS DOCUMENT IS PROPERTY OF BOGMATS AUSTRALIA AND ALL RIGHTS ARE RESERVED. IT IS COPYRIGHT AND SHALL NOT BE REPRODUCED, COPIED OR TRANSMITTED IN WHOLE OR IN PART FOR ANY OTHER PURPOSE WITHOUT THE EXPRESS WRITTEN PERMISSION OF BOGMATS AUSTRALIA PTY. LTD.

DRAWN BY:	XXXX
CHECKED BY:	XXXX
DRAWING NO:	XXXX
SHEET:	1 of 4
REVISION:	A